

**100,000**

HOURS RATED LIFE

**L80**

**50,000**

HOURS RATED LIFE


**L90**

**5**

YEARS  
WARRANTY



VENTURE  
LIGHTING



The Midibay Edge Pro 2 with its **streamlined design** is the next generation in LED lighting for warehouse and industrial applications. **Efficacy has increased** from 130 to **155 Lumens per Watt** from its predecessor, achieved by using twice the amount of market-leading Samsung LEDs. **Optional 90° prismatic refractor improves ground lux by up to 25%.**

# MIDIBAY EDGE PRO 2

# 135W Midibay Edge Pro 2, 850, D90


Order Code: IND227-D90

Photometric Data	
Nominal Lumens	20630
Colour Rendering Index (CRI)	80-89
Light Distribution	Symmetric
Lens / Reflector	Refractor lens

Life Data		
Rated Life (Hrs)	Ta = 25C	Ta = Tmax
	100000	-
Lumens Maintenance (Hrs)	Ta = 25C	Ta = Tmax
	B50	B50
L70	-	-
L80	-	-
L90	-	50000

Electrical Data	
Power	135-135
Microwave Sensor	No
Battery Type	
Light Sensor	No
PIR Sensor	No
Short Circuit Protection	Yes
Thermal Overload Protection	Yes
Flicker Free	Yes
Input (W)	146
Input (V)±10%	220-240
Voltage Type	AC
Power Factor	0.96
Electrical Class	I
Type of Wiring	Ending
Wiring X-sec (mm^2)	1.5
LED Nominal Current (mA)	700-700

Physical Data	
Warranty (yrs)	5
Ambient Rated Temperature Range (°C)	-25-40
Degree of Protection (IP)	IP20
Mounting Method	Pendant
Housing Colour	White
Housing Material	Steel
Reflector	None
Length (mm)	600
Width (mm)	480
Height/Depth (mm)	50
Lamp Type	LED not exchangeable
Reflector Material	Without reflector
Impact Strength	IK05



# 135W Midibay Edge Pro 2, 850, D90

Order Code: IND227-D90

Accessories	
ACS194 - Ball Guard Accessory. Reduces Lumen Output by 8%	
ACS153 - Programming Remote for SB Sensor	
ACS067 - Programming Remote for SH / SL Sensor versions	
ACS030 - Commisioning Remote for SH / SL Sensor versions	

Logistical Data	
Gross Weight (kg)	6.6