

















EMERGENCY BULKHEAD

EMG066 I EMERGENCY BULKHEAD

















Our Emergency Bulkheads are ICEL Endorsed and manufactured to provide full compliance with current standards, including BS 60598-2-22.

This product can be wired for either maintained or non-maintained operation and has IP65 protection, meaning that it can be used for indoor or outdoor applications.

FEATURES

3 Hours Emergency Duration

Lithium Iron Phosphate Battery

Maintained or Non-Maintained Operation

Self-Test as Standard

IP65 & IK10 Protection

PART NO.	WATTS (Maintained)	WATTS (Non-Maintained)	DESCRIPTION	ССТ	LUMENS	BEAM	WEIGHT (KG)	DIMENSIONS (L x W x D mm)
EMG066	5	3	Emergency Bulkhead, Self - Test	4000K	325	108x100°	1.9	355 x 109 x 61

ELECTRICAL DATA

MAINS VOLTAGE MAINS CURRENT POWER FACTOR REPLACEMENT BATTERY

220-240V 0.06 0.35 2 x 18650 Li-ion 3.6V 5.0Ah

ORDERING CODES

ACS382 Remote Control

ENVIRONMENTAL DATA

AMBIENT TEMPERATURE RANGE

0 - 40C

PERFORMANCE

CHARGING TIME INSULATION

< 24 Hours Class 2

